Dust mask

# **MATERIAL SAFETY DATA SHEET - 8 Point**

#### **SECTION 1 – PRODUCT INFORMATION**

Mascoat **Emergency phone:** (713) 465-0304 Houston, TX 77041 Fax: (713) 465-0302

> Date Reviewed: November 2011

**Product Name:** Mascoat Industrial-DTI

**Product ID:** MI-DTI

**Common Chemical Name:** Acrylic Insulation Coating

**Synonyms:** None **Molecular Formula:** Mixture

**Thermal Insulating Material HEALTH** 1 **FLAMMABILITY** 0 PHYSICAL HAZARD 0 G **Personnel Protection** Eye protection Gloves

## SECTION 2 - HAZARDOUS INGREDIENTS DETERMINED BY OSHA by PERCENTAGE

black. Custom tinting on

ACGIH TLV Cas Number **OSHA PEL Ingredients** % Range

This product does not contain any hazardous ingredients in reportable quantities

### **SECTION 3 – PHYSICAL PROPERTIES**

Color: White, light grey, grey, Form/Appearance: Thick emulsion

mixture

request. **Melting Point:** N/A Slight ammonia **Evaporation Rate (Butyl Ace =1):** Odor: **Boiling Point:** Appx. 212°F (100°C) Solubility in H<sub>2</sub>0: Dilutable Freeze Point 32°F (0°C) Volume Solids: 78-80% **Specific Gravity:** 0.63 **VOC Content:** 0.06 lbs/gallon Pounds/Gallon: 5.2-5.3 lbs/gallon

(7.6 g/liter)

Non-volatile Solids (weight): 53.0%

### **SECTION 4 – FIRE FIGHTING MEASURES**

Flash Point: Noncombustible

Auto ignition: N/A

**Extinguished Media:** (for dried film) carbon dioxide, water, dry chemical, or alcohol foam.

**Special Fire Fighting Procedures:** Full protective equipment including self-contained breathing apparatus should be used. If

water is used, fog nozzles may be preferable. Water may be used to cool closed

containers to prevent pressure buildup.

Liquid product will not burn but may spatter if temperature exceeds boiling point. **Unusual Fire and Explosion:** 

Extreme heat may cause closed containers to burst. Dried film of product is capable of

burning, giving off oxides of carbon/nitrogen.

## **SECTION 5 – REACTIVITY DATA**

**Stability Data:** Stable

**Incompatibility:** Solvents will coagulate the product. Extreme temperatures above 500°F (260°C) Conditions or Hazards to Avoid: **Hazardous Decomposition:** Hazardous polymerization will not occur.

**Corrosive Properties:** Not corrosive **Oxidizer Properties:** Not an oxidizer

**Chloride Properties:** None

### SECTION 6 - HEALTH HAZARD AND FIRST AID DATA

**Routes of entry:** skin-possible ingestion-possible inhalation-possible

**Health Hazards** Acute - In a confined area vapors in high concentration can bother some to personnel.

Extended periods of exposure without recommended PPE may result in health issues or

people susceptible to acrylic allergies.

Carcinogenicity: N/A

**First aid procedure:** Eye exposure - Flush eyes with water immediately. Get immediate medical attention.

**Skin contact** - Wash area with soap and water. If redness persists, seek medical attention **Ingestion** – If swallowed, dilute with water. DO NOT INDUCE VOMITING. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Get

immediate medical attention.

Inhalation – Move to fresh air. Aide in breathing if needed and get immediate medical

attention.

Notes to Physicians - None known

Medical Conditions Aggravated by Exposure- None known

Special Precautions - None

#### SECTION 7 - ACCIDENTAL RELEASE MEASURES

**Steps if material is released:** Spills should be contained and placed in suitable containers for disposal by a licensed

facility.

Waste Disposal Methods: Waste from this material is not hazardous as defined by the Resource Conservation and

Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed containers. Dispose of in accordance with Federal, State, and Local regulations.

Precaution in handling and storage: Use only with adequate ventilation. Avoid breathing vapor directly and spray mist

directly. Avoid direct contact with eyes. Wash hands after using. Protect against dust

which may be generated by sanding or abrading the dried film.

Other Procedures: Keep container closed when not in use. Transfer only to approved containers with

complete and appropriate labeling. Do not take internally. Keep out of reach of children.

**General:** Protect from freezing.

**Other:** Keep out of direct sunlight in storage area.

#### **SECTION 8 – PERSONNEL PROTECTION**

**Clothing:** Gloves, coveralls, apron, and boots as per any acrylic based system to prevent chronic

overexposure.

**Respiratory Protection:** Ventilation and dust mask recommended during application. If sprayed in confined area

respiratory equipment may be preferred due to slight ammonia odor and to help drying

process.

**Ventilation:** Local exhaust - preferable Mechanical (general) - acceptable

Protective Gloves: Preferred

**Eye Protection:** Spectacles with unperforated side-shields.

Other Protective Equipment: None needed

## **OTHER**

Special Handling: DO NOT LET PRODUCT FREEZE.

**Hazardous ratings:** Mascoat currently uses the National Paint and Coatings Association rating system. The

use of an asterisk (\*) in the HMIS rating indicates the potential for chronic health effects

HMIS: Health Fire Physical Hazard

1 0 0

Hazardous rating OSHA: The product is considered NON HAZARDOUS by the OSHA Hazard

Communication Standard.

**Trademark:** Mascoat® is a registered trademark of Mascorp, Ltd. - Houston, TX.

Important: While descriptions, designs, data and other information contained herein are presented in

good faith and believed to be accurate, it is provided for guidance only. Because many factors may influence the processing or application/use, Mascoat recommends that tests are made for the suitability of the product in the intended purpose. The intended use of this document is for health and handling procedures and not intended for an ingredients

list for reformulation.